

WISI VX 86

In-house amplifier



Description

At a glance:

- With passive return path
- Adjustable level and equalizer
- F-connectors
- Wall mounting
- Metal housing

Technical data

Downstream

Inputs	1 pcs.
Frequency range downstream	47...862 MHz
Gain downstream	18...21 dB
Noise figure downstream	<8 dB
attenuator downstream	0...18 dB
equaliser downstream	3...18 dB
interstage equalizer downstream	3 dB (constant)
Output level 1	96 dB μ V (DS, CENELEC 42 channels, flat)
Output level 2	98.5 dB μ V (DS, CENELEC 42 channels, 6 dB slope)
Output level 3	114 dB μ V (DS, EN50083-5, 3.Ord.)

Upstream

Frequency range upstream	5...30 MHz (passive)
--------------------------	----------------------

Connectors

F-socket	2 pcs.
----------	--------

General data

Operating voltage AC	230 V (50/60 Hz)
Power consumption	3.5 W
EMC	Class A, EN 50083-2
Dimensions (width x height x depth)	163x90x47 mm
Operating temperature range	-20...+55 °C
Protection class	IP20
Lightning protection	1 kV (EN61000-4-5, 1,2/50 μ s pulse)

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	166 x 143 x 50 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.871 kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	1.2 dm ³
Gross weight shipping unit	0.871 kg
EAN	4010056163457
Article number	16345
Customs tariff number	85437030